Sl. No.:

• .			
	 <del></del>	<del>т т.</del>	
Register	.		
Number			,

#### 2018

# TEXTILE TECHNOLOGY (Degree Standard)

Time Allowed: 3 Hours

[Maximum Marks: 300

CETET/18

Read the following instructions carefully before you begin to answer the questions.

#### IMPORTANT INSTRUCTIONS

- 1. The applicant will be supplied with Question Booklet 15 minutes before commencement of the examination.
- 2. This Question Booklet contains 200 questions. Prior to attempting to answer the candidates are requested to check whether all the questions are there in series and ensure there are no blank pages in the question booklet. In case any defect in the Question Paper is noticed it shall be reported to the Invigilator within first 10 minutes and get it replaced with a complete Question Booklet. If any defect is noticed in the Question Booklet after the commencement of examination it will not be replaced.
- 3. Answer all questions. All questions carry equal marks.
- 4. You must write your Register Number in the space provided on the top right side of this page. Do not write anything else on the Question Booklet.
- 5. An answer sheet will be supplied to you, separately by the Room Invigilator to mark the answers.
- 6. You will also encode your Question Booklet Number with Blue or Black ink Ball point pen in the space provided on the side 2 of the Answer Sheet. If you do not encode properly or fail to encode the above information, action will be taken as per commission's notification.
- 7. Each question comprises four responses (A), (B), (C) and (D). You are to select ONLY ONE correct response and mark in your Answer Sheet. In case you feel that there are more than one correct response, mark the response which you consider the best. In any case, choose ONLY ONE response for each question. Your total marks will depend on the number of correct responses marked by you in the Answer Sheet.
- 8. In the Answer Sheet there are four circles (A), (B), (C) and (D) against each question. To answer the questions you are to mark with Blue or Black ink Ball point pen ONLY ONE circle of your choice for each question. Select one response for each question in the Question Booklet and mark in the Answer Sheet. If you mark more than one answer for one question, the answer will be treated as wrong. e.g. If for any item, (B) is the correct answer, you have to mark as follows:

#### (A) ● (C) (D)

- 9. You should not remove or tear off any sheet from this Question Booklet. You are not allowed to take this Question Booklet and the Answer Sheet out of the Examination Hall during the time of examination. After the examination is concluded, you must hand over your Answer Sheet to the Invigilator. You are allowed to take the Question Booklet with you only after the Examination is over.
- 10. The sheet before the last page of the Question Booklet can be used for Rough Work.
- 11. Do not tick-mark or mark the answers in the Question Booklet.
- 12. Applicants have to write and shade the total number of answer fields left blank on the boxes provided at side 2 of OMR Answer Sheet. An extra time of 5 minutes will be given to specify the number of answer fields left blank.
- 13. Failure to comply with any of the above instructions will render you liable to such action or penalty as the Commission may decide at their discretion.

### SPACE FOR ROUGH WORK

er fought

1.	For a	fibre, when the moisture reg	gain increase	es, the ther	mal conductivi	ty.	•
	(A)	increases				· · · .	
	(B)	decreases	٠.		,		
	(C)	initially increases and then	decreases		• • • • • • • • • • • • • • • • • • • •		
	(D).	initially decreases and ther	ı increases	·		,	• ,
٠.			*	•			
		•					
2.	The e	effect of second order transiti	on temperat	ure in poly	ester fibre in		•
		reduction in birefringence	(	B) increa	se in birefring	ence	,
	(C)	increase in absorption of wa	ater (	D) increa	se in stiffness	t -	
			•	•		<i>;</i>	
3.	The r	nelting point of polyester is	, , ,	• •			• •
		higher than acetate	F	<b>*</b> .			
	(B)	lower than polyethylene					
• , ••	(C)	higher than polyethylene by	ut lower tha	n nylon			
	(D)	higher than wool and lower		*		* 3	. 1
4.	Amor	ng the following fibre which o	ne is having	serrated c	ross section?		
	(A)	cotton	_	B) silk	•		
		viscose	· · · · · (	D) kapok			
				· • • • • • • • • • • • • • • • • • • •	•		-
						, a	
5. ·	The r	najor part of the cotton fibre	is covered by	y	, `		
	(A)	Primary wall			er only		
-	C	Secondary cell wall	: 	D) Lume			
		booting out wan	. `	,	•		
·			· ·				
<b>6.</b>	A fib	re which is soluble in acetic a	cid in 2 min	utes at hoil	ing point in		•
·.	(A)	cotton	•	B) silk	TITE POTITO III	•	
	(A) (C)	wool		acetat	Δ.		
	, (O)	WOOT	V	, accial	. ·		•

7.	, 1110 1	dibt baccessiai symmetro inte is		<b>)</b>		
	(A)	polyester	<b>(2)</b>	nylon	•	
• • •	(C)	acrylic	(D)	polypropylene	<b>'</b> ,	•
			<i>,</i>			•
8.	Refra	active index is the ratio of velocity o	f light	in	to the veloc	eity of light
	in —	· · · · · · · · · · · · · · · · · · ·		•		
	(A)	material and vacuum	(3)	vacuum and mat	erial	
:.	(C)	atmospheric space to material	(D)	material to atmo	spheric space	
,			٠,			•
. ,.						
9.	Triac	cetate has negative birefringence value	e becau	se of	• •	
	(A)	isotropic arrangement of polymercha	ains			,
	W.	bulks acetate groups				:
	(C)	anisotropic arrangement of polymero	chains	:		•
	(D)	thin acetate groups				•
,			٠	•	•	, J
	•			•		
10.	Biref	fringence values of Poly Ethylene Tera	phthal	ate (PET) fibre is		•
• • • •	(A)	0.0188	(D)	0.188		
	(C)	1.88	(D)	18.8	. •	
	•					
11.	For s	showing dichroism, which one of the fo	llowing	condition is to be	satisfied?	•
•	-	the dye molecule must be asymmetr	ical			
	(B)	the dye molecule must be symmetric	eal		• •	• ,
* *	(C)	the dye molecule should not absorbe	d by th	e fibre		
	(D)	the orientation of chain molecules sl	ould b	e poor	• • •	• / . • . • . •
	•				,	
12.	Amo	ng the following, which fibre is having	negati	ive birefringence v	alue?	
	(A)	Ramie	æ/	Triacetate		· ·.
	(C)	Polyester	(D)	Polyethylene		

13.	The	decomposition temperature of vi	scose is		
		higher than cotton			
	(B)	lower than cotton			
	(C)	lower than cotton but higher t	han wool	• •	
	(D)	higher than cotton but lower t	han wool		
	· . ·				
			,		
14.	The	static change on card sliver after	lending is n	neasured by	•
•	(A)	Shirley moisture meter	(B)	Tog meter	
	SET.	Faraday cylinder	(D)	Galvanometer	
-	,		•	•	
	•				•
15.	The e	electrical resistance of protein fil	res are		
	(A)	lower than cellulosic fibres		higher than cellulosic fil	ores
	. (C)	equal to cellulosic fibres	(D)	equal to synthetic fibres	
				. :	•
-	e.				
16.	Ratio	of dry strength to wet strength	of viscose ra	yon fibre is	
	(A)	0.5	<b>48</b>	2	.•
	(C)	4	(D)	0.25	
17.	Rend	ing and bursting of fibre influen		properties of fabri	cs
	DOM	Drape and Handle	(B)	Frictional	,
	(C)	Electrical	(D)	Optical	
	:	'A	·( <b>D</b> )	Optical	
-	. ,				<i>:</i>
10		C1			0 Its alasti
		m fibre was extended to 30 mm ery % is	ana upon re	elaxation it reached to 27	.4 mm. its eiasti
	(A)	0.666	(B)	6.66	
		93.3	(D)	9.33	
	<b>V</b> ' .		<b>(</b> — )		

19	. The ri	peners of viscose solution i	s measured	by		
,		Salt index	· .	(B)	Xanthation ratio	
	(C)	Birefergence		(D)·	Sonic modulus	
				•		
	•					•
20.	Line	of breaking force across the	fibre would	d be lo	ng for ———	- polymer molecules.
	(A)	randomly aligned long		(B)	perfectly aligned sh	ort ·
	400	perfectly aligned long		(D)	randomly aligned li	near
-		•				•
٠.		•				
21.	Whiel	h one of the following is not	a fibre for	ming p	oolymer?	
•	(A)	A tactic polypropylene	•	(B)	Isotactic polypropyl	ene
	· (C)	Syndeotactic polypropyler	ie ′	(D)	Polyethylene tereph	nthalate
			•		:	
						,
22.	One v	way mass transfer of solver	t occurs in			
	W	dry spinning		(B)	wet spinning	No.
•	(C)	dry-jet wet spinning	š	(D)	melt spinning	
	•	$\epsilon_{i}$	*	•	* .	
		•	• .			•
23.		humidity has a significant	influence	on dra	awing of one of these	e synthetic fibres. The
-	fibre			<b>(D)</b>	,	
	(1)	Nylon 6		(B)	PET	`
	(C)	Polypropylene		(D)	Polyethylene	
		• •				•
	• •		•	_		
24.	The	crimps are introduced in Pl	ET staple fi			
		stuffer box texturising		(B)	edge crimping	
	(C)	false twist texturising		(D)	chemo texturising	
	٠		,			
•					,	
<b>25</b> .	The	fibre which is very difficult	to texture	by fal	•	3
*	(A)	polyester	• •	(B)	nylon 6	•
	(C)	nylon 66	•		polypropylene	· . , '

26.	The	high drips in melt spinni	ng occurs due	to	
	-	low quench air velocity	,	(B)	improper sand size
	(C)	die swell		(D)	draw resonance
٠					
27.	The	rapid quenching of nylon	6 from molter	ı state	e results in
,	(A)	$\alpha$ form		(B)	$oldsymbol{eta}$ form
	(C)	$\gamma$ form	•	0	pseudo hexagonal form
	-			,	
28.	<del></del>	fibre undergo	es cyclization	reactio	on before reaching its melting point.
		Acrylic		(B)	Polyurethane
	(Ć)	Polylactic acid		(D)	Cotton
	•		<i>,</i>	, ,	
29.	The 1	best feeder yarn for good	crimpability a	nd ref	ractivity in false twist texturising is
٠.	(A)	LOY	•	0	POY
	(C)	FDY		(D)	HDY
•		,		·	
	;	•			
30.	The o	cross-section of spinneret	used for produ	acing l	hollow fibre is
·. ·	(A)	C-shaped		(B)	Rectangular
1	C	Annular concentric	• .	(D)	Triangular
			· :		
31.	Ident	ify the fibre with negativ	e glass transit	ion te	mperature
	W	polyethylene		· (B)	nylon 6
	(C)	polyester	•	(D)	poly acrylonitrile
•	•.				
<b>32.</b> .	The I	Diethylene glycol formatio	on is maximun	n duri	ng ———— stage in PET synthesis.
• • •	(1)	poly condensation		(B)	trans esterification
	(C)	monomer synthesis		(D)	granule formation

33.		nich spinning system, t e outwards?	twisting of fib	res in y	arn making process ta	aken place from the
	(A)	Ring spinning	•		Rotor spinning	
	(C)	Wrap spinning		(D)	Airjet spinning	
	,					
34.	Whic	h part of the ring spinn	ing machine i	mparts	twist to the yarn?	
-	(A)	spindle		(B)	traveller	
	(C)	lappet thread guide	:	(D)	ring rail	
. •	٠.		.· ·			
35.	Bolst	er is a part of			•	
•	4	spindle in ring frame		(B)	flyer in roving frame	
	(C)	creel in ring frame		(D)	drafting system in rin	g frame
				•		
36.	,	a strongly twisted rovi	ng, what is t	he rang	e of break draft into l	pe given in the ring
	(A)	1.1–1.4		(B)	1.14-1.25	
	500	1.3–1.5	•	(D)	1.4–2.0	
<b>,</b> .					•	•
_		:			•	
37.	The	range of break draft giv	en in roving p	rocess i	s	
•	(A)	0.5-0.7			1.05–1.15	
	(C)	5–10	•	(D)	100–150	

(A)

(C)

**2–5**.

25 - 35

38.

9–18

(D) 40 and above

What is the range of over all draft of a comber drafting system?

- 39. The condition for lending disposition is
  - (A)  $v_1 < v_2$ ,  $v_2$  must be in the opp. direction of  $v_1$
  - $v_1 > v_2$ ,  $v_2$  must be in the opp. direction of  $v_1$
  - (C)  $v_2 = v_1$ ,  $v_2$  must be in the opp. direction of  $v_1$
  - (D) independent with  $v_1$  and  $v_2$  where  $v_1$  = flats/doffer,  $v_2$  =cylinder
- 40. Calculate the dtex value for cotton fibre of fineness value of 4.
  - (A) dtex = 4 / 0.394

 $\text{dtex} = 4 \times 0.394$ 

(C)  $dtex = 4 \times (0.394)^2$ 

- (D)  $dtex = 4 / (0.394)^2$
- 41. In case of automatic winding machine, theoretically maximum number of spindles per knotter is depends on
  - (A) speed of the machine

count of the yarn

(C) strength of the yarn

- (D) skill of the operator
- 42. In case of tappet shedding looms, which of the following type of heald movement is preferred for high speed looms
  - (A) parabolic and simple harmonic
- (B) parabolic and cyclodial
- polynomial and cyclodial
- (D) polynomial and simple harmonic
- 43. The increase in sley eccentricity value in shuttle loom
  - (A) increases the shuttle speed
  - increases the cost of the loom
  - (C) decreases the width of the loom
  - (D) decreases the vibration in the loom
- 44. Climax dobby is ———— dobby.
  - (A) single lift single jack

(B) double lift single jack

- (C) single lift double jack
- double lift double jack

45.	In mu	ıltiphase	weavir	ıg mach	ine warp	sheet	is form	ned by		·			
	. (A)	Heald s	haft					Rotating	g weaving	g rotor			
•	(C)	Tappet		1.			(D)	Jacquar	d	•			
	•	•				•					7		
,										,			
4.0	T	rondom m	rindina	machin	a tansid	n devi	ce is n	ositioned		1	he yar	n clear	rer.
46.		•	inding	· ,	ic, terrore	)11 ao 11		after				,	
	(A)	above	**				(D)	below		•			
÷		before					. (D)	Detow					
• • • •					,*								
				•	•	•	<b>~</b> .	•		. , -			
47.	Ratio	of lengt	h of yar	n in the	windin	g and b	oinding	g layers i	n a pirn				
		>1		.4			(B)	<1			• .	•	
•	(C) .	1					(D)	0.5	·	·		•	
					•	•		,		•			
,			·			•						i	
		,' <b>:</b>	tuo	tion is	10% <del>w</del> at	nickur	5.60%	warn she	et oven d	lrv mass	of 450	kg pa	ssec
48.		n size col ugh size l						waip one					
•	(A)	12			•			24					
	(C)	18		•	•		(D)	30					
	(0)				•		· · ·		•				. ••
	•									,			
					•	•				-	•	•	,
49.	A fa	bric wov	en fron	n a shu	ttle less	loom	with '	70 picks/:	min. The abric in l	loom ri length (r	uns at neter) :	a spec ner sh	ea c ift c
•		picks/mi urs is	n with	87% 100	uù erricu	ency. 1	ne br	i		(0118011 (1		P	
	(A)	66.6		t		•		60.6					
	•	30.3	. •		•		(D)			• •			
	(C)	. 50.5					(2)	0					
		•			·			•					
		•			•				•				•
50.	The	propellin	ng force	in the	weft car	rying s	ystem	in airjet	is enacte	d by			
	(A)	airjets	kept a	t both t	he ends			-	•		•		

multiple airjets kept along the pathway of weft

air propulsion and air suction at both the ends

air-propulsion at one end and air suction at other ends

(C)

(D)

51.	The wheatstone bridge network of strain at a frequency of	gauges	in the load cell is excited	l from an oscillator
	375 C/S	(B)	300 C/S	
•	(C) 275 C/S	(D)	325 C/S	,
	(6) 2.0 6/2	(4)	020 010	
52.	The minimum number of tests and lengt from long bast fibres is	h of tes — and –	t specimen (in) for Grey	yarn (single) spur
	(A) 20 and 10	(B)	20 and 5	
	50 and 10	(D)	50 and 1	,
		· .		
53.	Specific surface of a fibre is	٠ ,		
	(A) $\frac{2}{d}$		4	· .
	d	,	d	
	(C) $\frac{\pi d}{4}$	(D)	$\frac{4}{1}$	
	4		$\pi a$	
,		,		
<b>54</b>	Intype of sample ever	v indivi	dual in the population ha	as an equal chance
	of being included in it	<i>J</i>		
	(A) Biased sample	(45)	Random sample	•
	(C) Squaring technique	(D)	Zoning technique	
٠				
55.	In the context of Kawabata evaluation s with the units from Group II	ystem,	match the fabric proper	ties from Group I
•	Group I	• • •	Group II	•
	(a) Tensile energy	1.	gt. cm <sup>2</sup> /cm	
	(b) Linearity of load – elongation curve	2.	Percentage	
	(c) Bending rigidity		-	
•		3.	gt cm/cm <sup>2</sup>	
•	(d) Compressional resilience	4.	Dimensionless	
	(a) (b) (c) (d)		* *	
	(A) 1 4 3 2			
	3 $4$ $1$ $2$ $1$			
	(C) 2 4 1 3		:	•
	(D) 3 1 4 2		· .	
	· · ·			

56.	In the	e fast system, the fabric formability	is detern	nined by the prod	luct of fabric	•
	(4)	Bending rigidity and extension		· .	,	
	(B)	Bending rigidity and thickness				
•	(C)	Bending rigidity and weight			,	•
•	(D)	Bending rigidity and cover factor	•			
			÷		· ·,	
				. ·		
57.	Whiel	h of the following fabric strength pr	operty is	analysed by burs	sting strength t	tester?
	(A)	Terry fabric	(B)	Carpet fabric	•	
	VE)	Filter fabric	(D)	Silk fabric	•	
					,	
						, .
58.	The f	abric test length in case of strip test	is		•	•
	(A)	6 inches	(5)	8 inches	•	•
	(C)	10 inches	(D)	12 inches		
·	•	•	•	,		
			- '	•	·.	•
<b>59.</b>		hich of the following tensile testing letely eliminated?	g equipm	ent, the error pe	rcentage due t	o friction is
,	(A)	Tester working under inclined pla	ne princi	ple		
	(B)	Tester working under spring princ	ciple -	•		•
	(C)	Tester working under balance prin	_			· .
	- AD	Tester working under strain gaug	e princip	le	•	
		,			•	•
60.	Whic	h of the following tensile testing eq	uipment	works under pen	ıdulum lever pı	rinciple?
		Stelometer	(B)	Pressley streng	•	
	(C)	Cambridge extensometer	(D)	Instron tensile	tester	
•	( )	· · ·				
	•				,	
61.	Wha	t is the twist factor of 64 tex yarn h	aving 32	turns per meter	?	
	(A)	4	(B)	26	· ·	,
	(C)	98		256		
~			10	,		
I VIIIV	<u>ጥኩጥ/1                                   </u>	<b>6</b> .	ιZ			P

56.

62.	Tran	asfer printing of polyester belongs	to .	
	(A)	Resist style	(B)	Discharge style
	(C)	Colour discharge style		Direct style
		, , , , , , , , , , , , , , , , , , , ,		
63.	Cont	inuous dyeing machine		
1	(A)	Jigger machine	(B)	Soft flow machine
· ·	(C)	Winch machine	. 3	Padding mangle machine
			•	
	į,		•	
64.	Poor	rubbing fastness is associated wi	th cotton an	nd — dye combinations.
	(A)	Direct	(B)	Reactive
•		Vat	(D)	Bifunctional
٠.				
			-	
65.	The	efficiency of mercerisation is deter	rmined by	
	(A)	Methylene blue number	(B)	Copper number
	(C)	Iodine test		Barium activity number
66.	The 1	neutralisation of fabric using acid	after bleacl	hing is called
	(A)	Scouring	4	Souring
· ·	(C)	Antichlor	(D)	Reduction clear
	• • • • • • • • • • • • • • • • • • • •		•	
<b>67</b> . '	The o	lye which is water insoluble is	٠.	
•	(A)	Direct dye	(B)	Reactive dye
	(C)	Acid dye		Vat dye
			_	

68.	'Cond	ensed phase' mechanism of flame retardancy is achieved with
٠	4	Phosphorous containing flame retardants
•	(B)	Aluminium trihydrate and calcium carbonate based fillers
•	(C)	Boric acid based salts
	(D)	Halogen based flame retardants
<b>69.</b> ,	An ui	dyed fabric finished with cationic softener shows yellowing effect. It is due to
	(4)	Oxidation of the softener
	· (B)	Volatility of the softener
	(C)	Poor emulsion stability
	(D)	Thermo migration of dyes
70.		ere tendering and disintegration of fabric occurred after sodium hypochlorite bleaching. nay be due to
	W.	traces of iron and copper present in cotton
	(B)	action of stabilizer
	(C)	action of buffer
,	(D)	action of salts
. •		
<b>71</b> .	The b	ioscouring of cotton can be carried out mostly by
	(4)	Alkaline pectinase
`; `	(B)	Acidic cellulase
	(C)	Neutral cellulase
	<b>(D)</b>	Amylase
72.	Amor	ng the following bleaching agents, bleaching of cotton is carried out in acidic condition
	(A)	Calcium hypochlorite (B) Sodium hypochlorite
	(6)	Sodium chlorite (D) Hydrogen peroxide

73.	Whi fabr	ch of the following relation is ic?	used to	calcul	ated the tightness fact	or value of weft kni
	(A)	loop length in $cm/\sqrt{tex}$	٠			
	· (B)	loop length in cm/tex				
• •		$\sqrt{\text{tex}}$ / loop length in cm				· ·
	(D)		• .			
•	(D)	tex / loop length in cm				
• •			•	•		
	· ·					
74.	Invis	sible fleecy fabric is a		— fab		· · · · · · · · · · · · · · · · · · ·
•		Single jersey	,	(B)	Double jersey	•
	(C)	Flat knit		(D)	Wárp knit	
•	,					
,						
<b>75</b> .	The	purpose of 'splice mark' on the	spreadin	g tabl	e is	
	(A)	to regulate the thickness of t	he lay	,		
,	(B)	to regulate the width of the f	abric	\$	,	
	(C)	to indicate the faults in the f	abric '			
, .		to indicate the joining point	of the fab	rics	•	·
٠.	;			٠		
			•			
76.	Notel	her is one of the				
·	(A)	Pattern making tool		(B)	Lay cutting tool	
	4	Marking tool		(D)	Fabric spreading tool	
	•					
						· ·
77 .	Whiel	h of the following stitch class i	a mand for	n Thair		· ·
••.	(A)	lock stitch	s useu 101	CDAIS		
21	(C)	multi thread chain stitch		(D)	chain stitch	•
	(0) /	mum meau cham shich		(D)	over edge chain stitch	
, •	•.		•			
. •	÷					
8.	'Over	-lock welting' type of over edge		itch is	formed by the combin	ation of
. (	(1)	one needle and one looper thr		•		
	(B)	one needle and two looper thi				
	(C)	two needle and one looper thr	ead			
	(D)	two needle and two looper thi	read	• .		• .

79.	Which	n of the following is not the part of l	line plann	ing process?		•
•	(A)	Evaluating merchandise mix			•	
	(B)	Planning merchandise budget	•			
	500	Determining the styles in the line		· ·	•	,
,	(D)	Analysing and cydating merchand	lising plar	ı		,
•	,					١.
			•		•	
80.	It is u	used to get fancy effects by using co	loured ya	rns	· 	•
	4	Tuck stitch	(B)	Float stitch	•	
	(C)	Purl stitch	(D)	Knit stitch		
•						
						•
81.	Analy	yzing technical design of an appare	l is one of	the activities of		٠
•	(A) <sup>1</sup>	Line planning	(P)	Line developme	ent	
	(C)	Line presentation	(D)	Line loading		
,					•	
				•	•	
82.		eptual mapping is a diagrammatic	techniqu	ne used by asset	markets that a	ttempt
		ally display the perceptions of ———		Potential		
• .	(A)	Need	(D)	Varying	,	•
	(C)	Selecting	(D).	varying		
,	•					
83.	Тет	porary silicone finishing of fabric is	importan	t for		•
	(A)	Pedalling type sewing machine	<b>F</b>			,
. •	(B)	Motor driven low speed sewing m	achine			
	(B)	Motor driven high speed sewing in			•	
•	. 🕠 .	Pedalling type high speed sewing				_
•	(D)	redaining type ingh speed sewing	macmine	• • • •	` .	
	,		• .			
. 04	ar e	de thread aboin stitch halongs to al	aga,			
84.	Sing	tle thread chain stitch belongs to cla		200	•	
	. 100	100	(B)	200		

(D)

400

(C)

300-

85.		woven web from cotton fibr	es can be	prefera	ably formed	d by		— bonding
	(A)	Thermal and mechanical		٠.	•			
	P	Mechanical and chemical		,		•		
	(C)	Thermal and chemical	•	.,			•	
	(D)	Mechanical and Interlace	ment	·	,			-
·.								
86.	whil 0.00	omplete to and fro strokes of e the delivery lattice speed 13 Ne and the actual draft non woven web formed is	l is main	tained a	at 7m/min	. If the har	k of the	feed lap is
		114		· (B).	111		•	
·	(C)	124	•	(D)	134			
•	•		•					
			:					
87.	The	major limitation of poly chlo	ropene bi	nders				· . · .
, .		Crystallisation there by ir	_		ness	•	•	•
	(B)	Not resistant to acids			•			•
	(C)	Undergo discoloration						٠ .
*	(D)	Poor weather resistant						
•								
88.		most preferred polymer to tant barrier and heat sealin			xtrusion co	pating of no	nwovens	with water
	U.	LDPE	· .	(B)	HOPE			•
•	(C)	HMWPE		(D)	PP		· ·	• .
	•			ı *		•		
8 <b>9</b> .	For v	vipes, the preferred bonding	is				. :	•
:	(A)	needle punching			<ul><li>spray bon</li></ul>	ding		
	(C)	bulk calendering	•	(D)	laminatio		•	
•		•				*		

,	body	of filter medium due to electrostatic	forces is		٠,
	(A)	screening		depth filtration	•
• • •	(C)	cake filtration	(D)	sieve filtration	
			•		• •
91.	In ca	se of basal embankment, the major f	actor to	be considered is	ī
		stress relaxation	(B)	fatigue	
•	(C)	mechanical conditioning	(D)	creep	
•				•	•
92.	$^{0}_{L}90$	in case of testing of Geotextiles relat	e to		
	(1)	holes in textile substrate	(B)	diameter of particles	
	(C)	velocity of air used for testing	(D)	penetration efficiency	
	•		•	•	
·					
93.	Hot §	gas filtration of around 1000°C can be			——— fibres.
	· (A)	Polypropylene	(B)	Polyethylene	
, ,	(	Ceramic	(D)	Polyester	
			4-1		
94.	On 11	mpact, the full deployment of air bag		FF 1.	
	(2)	55 milliseconds	(B)	55 seconds	
	(C)	0.5 milliseconds	(D)	5 milliseconds	
. ,			,		
95.	One	of the most popular instrument for s	ingle fib	re measurement is	
50.	Circ	Shirley comb sorter		B.F.T sorter	
. •	(C)	Reynolds and Branson tester	(D)	W.I.R.A. crimp tester	
	, (0) ,	neyholus and Branson tester	.( <b>D</b> )	**.1.10.21. CIMIP 005001	
96.	The	dead weight suspended from the en	nd of th	e bottom loop of the c	oupling to keep the
		less pulled down when not required t			<del>-</del>
	X4	Lingo	(B)	Griffe	
	(0)		· (D)	To a la a a d	

The mechanism by which particles are captured through attachment to the firbes within the

90.

01.	.111 ()	banne, prime coat is defined as	,	•	•
	· VI	Direct material cost + direct labour of	cost +	direct expenses	
	· (B)	Direct material cost + direct labour of	cost		
	(C)	Direct material cost + direct expense	es		
:	(D)	Direct material cost – direct labour o	cost + c	direct expenses	
					•
	. :				
98.	It de	als with recording the time and rate of	worki	ing under specific conditi	ons
	· (A)	Method study	(B)	Work sampling	
	(C)	Predetermined time standard		Time study	
,					
			٠,		
99.	Adve	ertisement cost is an example for ———		voverheads.	
	(A)	Factory	(B)	Administrative	
•		Selling and distribution	(D)	(A) and (B)	
			. (2)	(13) 4114 (15)	
•					
100.	The	technological aspect in a textile indust	rvie e	un avamnla for	——— in TQM
100.	axio		, , у 15 с	in example for	III TQW
	(A)	Commitment	(B)	Involvement	•
•		Scientific knowledge	(D)	Motivation	•
101.	It de	als with behavioral issues as well as te	chnica	l issues is an industry	
	(A)	supply chain management			
	0	management information system	,		
	(C)	business process reengineering			
,.	(D)	quality control circle			
			•		•
102.	The o	consumers may share a strong need th	nat car	nnot be satisfied by an e	Existing product is
·	called		· ·	and so savisized by all t	vrighting brounce is
	(A)	Negative	(B)	Non-existent	
, .	100	Latent	(D)	Decline	
	•				

103.	The two important natural protein fibres are ———————————————————————————————————									
	(A)	cotton and jute	(B)	silk and cotton						
		wool and silk	(D)	wool and casein						
104.	First	order transition temperature of Ny	lon 6,6 fib	re is						
	(A)	40°C	(B)	80°C						
	(C)	230°C	45	260°C						
		, f	,							
		•								
105.	XRD	photograph of a cotton fibre would l	oe having							
	(A)	sharp spots	(B).	slightly diffused rings						
•	400	slightly diffused broken rings	(D)	diffused						
	<i>•</i>			•						
		•	-							
106.	Conv	olution in cotton fibre is because of	•							
	(A)	fibrils	(B)	primary wall						
		cell sap evaporation	(D)	fibre degradation						
			,	•						
107.	Fibre	e that is soluble in 80% formic acid								
٠.	(A)	Acrylic	(B)	Poly Ethylene Terephthalate (PET)						
	100	Nylon	(D)	Cotton						
108.	Fine	structure model of viscose rayon file	re is							
	(A)	fibrillar	(B)	fringed fibrillar						
	(C)	micellar	. 07	fringed micellar						
	,				•					
			•							
109.	Jute	fibre is classified as natural cellulo	sic —	fibre.						
-55.	(A)	bast unicellular	(P)	bast multicellular						
	(C)	leaf unicellular	(D)	leaf multicellular	•					
	\-\ <u>'</u>									

	(A)	lower than cotton		v *	•	•
	(B)	higher than polyester but lower than	n cottoi	n -	,	
-	4	higher than cotton				
	(Ď)	higher than cotton and glass				
				•		
				•		
111.	The	wave length of the electrons used in el	ectron	microscopy	is	
•	(A)	10 Å	(B)	5 Å		
	(C)	1 Å	1	$0.05\mathrm{\AA}$		
	. 4		•			
	•		•	•		· . ·
112.	In a	fibre, the length of the micro fibrils is			•	
	(A)	1 μ	(B)	$0.1~\mu$		,
•		100 Å	(D)	$0.1\mathrm{\AA}$		
	٠.					
• •	•					
113.	The c	orientation factor of Ramie fibre is	,		,	
	(A)	0.54	(B)	0.88	,	
	(C)	0.74	(12)	0.97	٠.	· · · · · · · · · · · · · · · · · · ·
, `	•					
	,					
14.	The 1	proportion of non crystalline regions of	f the na	ative cellulo	ose is	
	(A)	one fourth of the total in native cellu	ılose			
	(B)	one third of the total in native cellul	ose			
	(C)	half of the total in native cellulose			,	e Francisco
	(D)	three fourth of the total in native cel	llulose			
			. •		•	•
,			•			
15.	Amo	ng the following, which one of the fibre	e is con	pletely cry	stalline?	•
	(A) .	cotton	(B)	nylon		
	(C)	glass		asbestos		· .
						•

110. The density of asbestos is

	(A)	refractive index along the fibre axis
	(D)	two principal refractive indices
. •	(C)	refractive index across the fibre axis
	. (D)	refractive indices of $x, y$ and $z$ axis
•	•	
117.	How The	n a fibre was subjected to 10% elongation, it developed a load of 120 gram-force. ever, the load decreased with time through the fibre was held in the extended position. cause for such decrease in load is because of ———————————————————————————————————
·	(A)	molecular stress and stress relaxation
		molecular readjustment and stress relaxation
÷	(C)	molecular stress and creep
-	(D)	molecular readjustment and creep
	•	
118.	Stati	c charge development in textile fibres can be overcome by
	(A)	decreasing electrical conductivity (B) decreasing humidity
•	(C)	increasing disorder increasing electrical conductivity
119.	The s	second order transition temperature of polyester is
	(A)	-5°C (B) 50°C
•		70°C (D) 100°C
•		(5) 100 0
	•	
120.	The r	noisture absorbing fibres cannot be heat set, because
٠.	(A)	the bond between the molecules are very strong
	(B)	the cross links between the molecules cannot be broken
	VO	the cross links between the molecules are broken and reformed on the wetting and drying of fibres
•	(D)	the melting point is very high
CET	ΈΤ/18	ρ

116. Birefringence of a fibre in determined by measuring the

121.	When the fibre is tested in standard conditions, the tenacity in g-wt/tex of cotton fibre is
. *	(A) higher than flax
	lower than flax but higher than jute
	(C) lower than acetate
	(D) higher than flax but lower than jute
122.	Which one of the following statement in suitable for bast fibres when compared with cotton
	fibre?
	poor recovery from strain and it can withstand large stress
	(B) good recovery from strain and it can withstand small stress
	(C) poor recovery from strain and it can withstand small stress
	(D) good recovery from strain and it can withstand large stress
123.	After recovery by the first test to measure creep, if the same load is applied again to a fibre,
	the rate of creep is  (A) similar to the first test
	less than the first test of the specimen
	(C) greater than the first test of the specimen
· ·	(D) equal to secondary creep
124.	The tensional winitity of a fibra can be obtained intermed of
144.	The torsional rigidity of a fibre can be obtained interms of
	(A) tensile modulus shear modulus
	(C) bending modulus (D) specific stress
125.	The neutral comonomer in acrylic polymer is
	Methyl acrylate (B) Sodium allyl sulphonate

Sodium methallyl sulphonate

(D)

Itaconic acid

- 126. Which one of the following is mechanical texturising process?
  - False twist texturising

- Simultaneous draw texturising
- (C) Sequentional draw texturising
- Air Jet texturising
- The process of drawing of as-spun filaments to impart orientation is typically carried out at temperatures
  - above glass transition

- (B) below T<sub>g</sub>
- (C) near melting point (Tm)
- (D) at crystalization temperature
- In the context of application at spin finish to synthetic fibres, the incorrect statement among 128. the following is
  - (A) spin finish dissipates static charge
  - spin finish reduces fibre breakage in carding (B)
  - spin finish reduces the stiffness of the fibre
  - spin finish reduces the nap generation tendancy in fibres (D).
- Which one of the following increases on increasing water concentration (catalyst) during 129. nylon 6 polymerisation?
  - molecular weight

time of polymerisation (B)

- - end groups

- (D) rate of polymerisation
- Incase of melt spinning, if W is the mass through put rate,  $\rho_0$  L is the density of melt,  $d_0$  is 130. the spinnerette hole diameter n is the number of filaments, the average extrusion velocity  $(v_0)$  is given by expression

$$v_0 = \frac{4W}{n\rho_0\pi \, d_0^2}$$

(B) 
$$v_0 = \frac{4\rho_0}{nW\pi d_0^2}$$

(C) 
$$v_0 = \frac{4d_0^2}{nW\pi\rho_0}$$

(D) 
$$v_0 = \frac{4\rho_0 n}{W\pi d_0^2}$$

·131.	Forn	roducing a coarse count yarn from short staple trashy cotton sliver, the most suitable
101.	rotor	
ν*	(A)	large diameter rotor with narrow groove
	(B)	small diameter rotor with wide groove
	(C)	small diameter rotor with narrow groove
٠ ,		large diameter rotor with wide groove
	,	
	•	
132.	35 K	g raw cotton is mixed with 65 kg polyester in the blow room feed. If the raw cotton
	conta	ined 6.5% trash which was removed completely in the blow room and carding process,
.•	the %	blend proportion of cotton and polyester in the carding sliver is
	(A)	60% and 30% (B) 30% and 60%
	(C)	67% and 33% 33% and 67%
	, ,	
	,	
133.	In rin	ng spinning, the tension in yarn is the maximum
•	W/	In winding zone
,	(B)	Where the balloon radius is the maximum
	(C)	Just below the lappet guide
	··(D)	Between the lappet guide and front roller
•		
134.	The d	lraft in the roving frame is about
202.	(A)	100
•	(C)	3 (D) 30
	(-)	
٠.	. 4	
195	Tmo	3 over 3 drafting system, the ratio of the nip to nip distance between middle rollers to
135.		rollers and middle rollers to front rollers would be
		>1 (B) <1
	(C)	$_{1}$ (D) $_{0.5}$
	, ,	
19 <i>6</i>	Paris	of mechanical draft to theoretical draft would be
136.		and the second s
•	(A) (C)	
	(C)	1 (D) 0.5
		•

105	, . TT	* 1		-							;	
137.		much noil% is it $0.5 \text{ mm}$ ?	ncreased	when	the d	depth of	thė	top	comb	penet	ration i	S
	(A	2%			· /D\	. 407		,	•		,	
, ,		•	•	•	(B)	4%	,			•		
•	(C)	6%		•	(D)	10%						
•				; ;.		•				•		
					•	•			,			
138.		ectilinear comber, w	-	ippers a	re ope	n, the len	gth of	lap f	eed by	the fee	d roller i	s
•	betwe		and ——		_	,	·.				•	
	(A)	4 cm, 6.5 cm			(3):	4 mm, 6	3.5 mm	<b>1</b>	,	٠.		. •
	(C)	10 mm, 12.5 mm			(D)	10 cm,	12.5 cn	<b>1</b>			•	
	• .											
	• . •	. •				•				•	•	
139.	Amor	ng the following whi	ich one is	s more	soft w	ith respe	ct to t	top r	oller's	degree	of shore	е
٠	hardı	ness?								•		
		60°–70°			(B)	70°–80°		•	•			
	(C)	70°–90°			(D)	above 9	0°					
	,			, •	,	··.	*	,				
. *	•		٠.						•			
140.	Whic	h one of the following	g is the ad	lditional	effect	of draft?						
	(A)	neps formation			(B)	straight		of fib	re hoo	ks		
•	(C)	fibre entanglement	•	. •	(D)	fibre br	_		•	•		
			•			•	J					
	-			·		,	•					
141.	Inar	roum ouoss section th		-C C:1	- ()							
141.	III a y	varn cross section, the	e number	ormore		<u>-</u>						
		Texyarn/Texfibre	•		(B)	Texfibre/				.•		
. `	(C)	$Tex_{fibre} \times Tex_{yarn}$	٠.	`	(D) <sub>.</sub>	(Texyarn/	Texfibr	e) <sup>2</sup>	. •			
٠,	٠.			•		•					·	
	. `	•			•	~∙ .				•		
142.	The i	ntimate blending car	be obtain	ned by		•					•	
	(A)	lap blending			(B)	web ble	nding	:	٠		,	
٠	(C)	sliver blending		•	(D)	fibre ble	ending		· ·	,		
			,				•					

143.	In — pick.	Jacquard, all the warp threads reaches the bottom of the shed on even
	pick.	single lift, single cylinder (B) double lift, single cylinder
•	(C)	double lift, double cylinder (D) open shed
	(5)	
	•	
144.	In ca	se of automatic yarn clearing machine, clearing efficiency (CE) is defined as
	(A)	$CE = \frac{\text{Number of faults detected in the yarn}}{\text{Total number of faults in the yarn}} \times 100$
	(B)	$CE = \frac{Number of objectionable faults detected in the yarn}{Total number of faults in the yarn} \times 100$
	4	$CE = \frac{Number\ of\ objectionable\ faults\ detected\ in\ the\ yarn}{Total\ number\ of\ objectionable\ faults\ in\ the\ yarn} \times 100$
	(D)	$CE = \frac{\text{Number of faults detected in the yarn}}{\text{Total number of objectionable faults in the yarn}} \times 100$
145.	In a diam	tex system, if the change in mass is 100%, what will be the approximate change i
	(A)	20% (B) 30%
•	المناكب	40% (D) 50%
	· .	
146.	The d	raft plan in woven fabric design analysis indicates
	(A)	Interlacement of warp and weft
	(B)	Order of drawing warp through reed
	(2)	Number of heald shaft required for weaving
	(D)	Number of weft per design repeat
147.	Which	n of the following statement is not correct with respect to crepe weave woven fabrics?
	(A)	High twist yarn is used

They formed by insertion of one weave over other weave

They have prominent twill effect

Fabric surface is not smooth

(C)


(D)

	(A)	narrow loom	(B)	tape loom	
	(C)	spacer machine		circular loom	
		: •			
149.	į	twill fabric, the rate of achievement of ards is 1, ends per cm is 42 and picks p		upwards is 2, rate of advancement of twill is 21. Calculate the twill angle	L
	(A)	45°	(B)	11°	٠
		76°	(D)	60°	
:	. •		•		
150.	The	weave that produces perforated fabrics	and d	distorted thread effects is	
	(A)	Huck-a-lack weave	(B) ·	Basket weave	
	(C)	Hopsack weave		Mock leno weave	•
•			,	·	
151.		•	en the	e shuttle fails to reach the shuttle box (or	)
		tle trap in the warp shed is known as			1
	(A)	shuttle checking mechanism		· ·	
	(B)	warp stop motion			
٠٠.	(C)	weft protector mechanism	•		
		warp protector motion			
	٠.				
152.	The	power required to drive a loom working	g on o	pen shed principle is less, because	
	(A)	heald weight is less			
	(B)	speed is maximum			
	(C)	used only for simple weaves			
	(0)	unnecessary movement of the thread	ls are	avoided	

Jute sacks in tubular form are produced from

148.

153.	Katio	of grab strength to	strip strength is	tne nigi	nest wn	en iabric	extension	1 (%) IS	
	(A)	0		(B)	5			, ac	
•	(C)	10	,	D	15			•	
			,			•			
			•	• .	•		. ,		
1 E 4	A 00	5 denier viscose yar	n haa a bwaaking	atuon at l	of 7 51	V. Tho vo	nn tonocit	r in CNL	dtor ia
154.	•		n nas a breaking		101 7.51	N. The ya	m tenach	,y 111 O1N/	diex is
•	(A)	1		(B)			•		•
	( )	3 · · ·		(D)	30	•	•		
						•		•	
•			,	•					
155.	Whic	h of the following fa	bric is used for a	ir bag ap	plicati	ons at the	e driver si	de?	
	SA FO	25 imes25 twill weav	e polyester fabric		•			•	
	(T)	$46 \times 46$ plain wear	ve Nylon 6, 6 fabr	ìc		. *			٠, .
	(C)	$25 \times 25 \text{ rip stop N}$	ylon 6, 6 fabric		*				
,	· (D)	$41 \times 41$ plain wear	ve polyester fabric	2		٠			
	•			•					
	* .				*				•
156.	The r	property of fibres the	at AFIS does not	measure	e is		•	•	
100.	(A)	Fibre length		(B)	•	maturity	• •	•	
	(21)	Short fibre index		(D)	Nep co				
•		bhort libre index			Ttop o	,		•	
·				•	•				
	. •							•	,
157.		vibroscope method	for determination	n of fib	re finer	ness does	not take	into ac	count of
	speci	•		, (D	Тът 11	·	1		
	(A)	Natural frequency				e strengt	n .		
	(C)	Tension		(D)	Lengt	<b>n</b>			
-				•		• •			
					,			•	
158.	Samp	ole selection for test	ing requires			•			<u>-</u>
•	(A)	Biased approach to	o meet population	n mean					
,		Random approach	to meet population	on mean	r <b>"</b>				•
	(C)	Random approach	to not to meet po	pulatior	n mean	-4			•
	(D)	Biased approach to	o not to meet pop	ulation	mean	•		•	
		<u>, , , , , , , , , , , , , , , , , , , </u>			• .	•			



- In general, the floating fibre percentage in the drafting systems is calculated from the - data.
  - (A) Shirley comb sorter

- Sledge sorter
- Schlumberger comb sorter (C)
- Digital fibro graph
- In sampling process, the relationship between standard error of the mean (SEM) and the 161. standard deviation of the population (SDP) is
  - $SEM = \frac{SDP}{n}$ (A)

(D) SEM =  $\frac{\text{SDP}}{\sqrt{n}}$ (D) SEM =  $\frac{\sqrt{n}}{\text{SDP}}$ 

(C)  $SEM = \frac{n}{SDP}$ 

- The zoning sampling method is used to determine
  - Properties of sliver (A)

Properties of fibre

(C) Properties of yarn

- Properties of fabric
- 163. Levoglucosan is related to finish.
  - Antistatic

(B) Crease resistant

Fire retardant

Soil release (D)

- Reactive printing of cotton uses
  - $\rm Na_2CO_3$

(B) NaClO

NaClO<sub>2</sub>

(D) NaClO<sub>3</sub>

According to K-M theory, the concentration of dye in fabric is directly proportional to 165. [R-Reflectance from sample] (A) (C)  $\frac{1}{R}$ Nylon/Wool blends are often dyed with 166. Milling type acid dye Bifunctional reactive dye (B) Hetero functional reactive dye (C) Homo functional reactive dye (D) - is used as reducing agent in vat dyeing. 167. Sodium hypochlorite Sodium hydrosulphite (B) Sodium bromite Sodium chlorite Which one of the following is not true about acid dyes? 168. (A) Acid dyes are sodium salts of organic acid Acid dyes have affinity to protein fibres (B) Glauber salt is used as levelling agent during acid dyeing (C) Acid dyes are relatively difficult to dissolve in water - is the measure of strength of bonds by which dye is held to the fibre 169.

(B)

(D)

Entropy of dyeing

Chemical potential

Heat of dyeing

Half dyeing time

170.	The r	nost commonly used discharging agent is
. '	4	formaldehyde sulphoxalates
	(B)	sodium dichromate
	(C)	pottasium dichromate
٠.	(D)	glycerine
	, , , , , , , , , , , , , , , , , , ,	
171.	Whic	h one of the following transfer printing is more preferred for garment panel units?
	(A)	sublimation transfer
•	(B)	melt transfer
	· (C)	film release
•	(D)	wet transfer
•		
`.		
172,	Whice timin	ch of the following statement is true for a rib knitting machine that works under delayeding?
	(A)	Cylinder needle first comes to the feeding position
,		Both cylinder and dial needle simultaneously reaches the feeding position
•	(C)	Dial needle first reaches the knock-over position
٠.	(D)	Both dial and cylinder needle simultaneously reaches the knock over position
•		
	•	
173.		knit fabric with tuck stitches is then the knit fabric with kni hes only.
	(A)	Thinner Wider
•	(C)	Less porous (D) Highly extensible
, e		
174.	Knit	ting needles with different butt sizes are used in circular knitting machine having
	.(A)	Swing cam (B) Multi cam
	(2)	Split cam (D) Pattern drum

175.	. The	width of the long groove in the sewing needle is -	of blade	diameter.
	(A)	15% (B) 30%	, ,	
	4	45% (D) 60%		•
176.	•	ingle needle lock stitch machine, the preferred fee	ed-dog tooth pitch for sewi	ng medium
		ght fabric is		
	(A)	1 mm 1.5		
	(C)	2 mm (D) 2.5	mm	
177.	In do	ouble needle lock stitch machine, the feed dog has	motion	
	(A)	Circular		
•	9	Eliptical		
	(C)	Lateral		
	(D)	Up and down	•	<b>,</b>
				,
				,
178.	Majo	ority of sewing machine prefers 'Z' twist yarns than	'S' twist yarns because	
	(A)	they have high strength	, ·	• .
	(B)	they are highly flexible		
•	(C)	they have high elongation		
		they don't loose twist		•
	<b>•</b>			·*.
•				
170				•
179.		of the limitation of polyester wrapped cotton core s	pun thread is	
	(A)	poor elasticity		
	(B)	high cost		
	(C)	low work of rupture		
•		high needle heat generation		

	· (B)	weather resistance, water impermeability and retention properties
	100	water penetration and retention properties and durability
	(D)	weather resistance, sunlight transparency, water impermeability
	٠.	
181.	Widel	ly used fibres in geotextile applications are
	(A)	Polypropylene and Polybutylene
	(B) ·	Polyethylene and Polybutylene
	4	Polypropylene and Polyethylene
	(D)	Polyethylene and Polyvinyl alcohol
182.	Cyclic	c loading performance of a technical fibre depends on
	(A)	Elasticity
	(B)	Elasticity at break
	(C)	Elasticity at low extension
		Elasticity even at high extension
183.		ile strength of Ultra High Molecular Weight Polyethylene (UHMWPE) in gram per er is approximately
	(A)	0.55 (B) 5.5
	107	55 (D) 555
184.	Endı	use property that is preferred from nonwovens
		Absorbency (B) Thermal conductivity
-	(C)	Strength (D) Density
CET	re <b>T/1</b> 8	34

Requirements of technical fabrics for soil mat are

(A) weather resistance, opaque to sunlight and insects entry restriction

180.

- In calendering process, if the contact area is 30 mm<sup>2</sup> and the production speed is 300 m/min. 185. The estimated contact line is
  - (A) 0.6 millisec

0.06 millisec

0.006 millisec (Ċ)

- 6 millisec
- For the given fibres, heavily entangled fabrics can be produced by hydro entanglement at low pressure and energy for
  - viscose

(B) glass

carbon

- (D) polypropylene
- 187. In case of needle punching, the punch density is calculated using

 $[P_d-punch density, n_n=number of needles per cm, P=fabric production speed, S_f=punch$ frequency

- $P_{\rm d} = \frac{n_{\rm n} \times s_{\rm f}}{P}$

(B)  $P_d = \frac{n_n \times P}{s_c}$ 

- (C)  $P_{d} = \frac{n_{n}}{s_{f} \times P}$
- (D)  $P_d = \frac{P \times s_f}{n}$
- Which one of the following statements is 'Incorrect' about fibre dispersing behavior in wet lay system?
  - The dispersing property of fibres deteriorate with an increase in the fibre fineness ratio
  - The dispersing property deteriorate with decrease in fibre stiffness (B)
  - Fibres which are non crimped form homogenous suspension (C)
  - Wettability of fibres in liquid medium does not influence dispersion
- The type of reinforcement in which a tensile force is applied to the geotextile that is 189. surrounded by soil on both sides is
  - anchorage reinforcement
- membrane reinforcement

(C) shear reinforcement normal reinforcement

•	•			•	
190.	ŢSS i	is an effluent means			
	(A)	Total soluble solids	(3)	Total suspended solids	
	(C)	Total sinking solids	(D)	Total soap solids	
	٠.				
191.	Whic	h one of the following is a secondar	ry treatme	nt process?	•
	(A)	Equalisation	(B)	Neutralisation	
	(C)	Chemical coagulation		Trickling filter	•
•					
192.	The l	Biological oxygen demand in a text	ile process	ing industry is greatly reduced at	
	(A)	primary treatment			
•		secondary treatment			
	(C)	teritary treatment		•	
٠.	(D)	preliminary screening	•		
	(15)	prominary sorooming			
102	ml. o	oolows and owner domand in an of	fluort oor	ho moderno d voice m	
193.	The C	colour and oxygen demand in an ef			
-,		Bleaching effluent	(B)	Scouring effluent	
	(C)	Desizing effluent	(D)	Printing effluent	
					•
194.	An e	ffluent which is characterized by h	igh amour	at of hydrolysed dyes and dissolved salt	s is
	(A)	disperse dyeing effluent			•
	<b>(B)</b>	milling acid dyeing effluent			•
	(C)	levelling acid dyeing effluent			
		reactive dyeing effluent	•		
			•		

195.	Marker Efficiency % is calculated as
•	(A) Area of total marker Area of marker used for garments
	(B) Area of total marker – area of marker used for garments
	$\frac{\text{Area of marker used for garments}}{\text{Area of total marker}} \times 100$
:	(D) Area of total marker + Area of marker used for garments
196.	The total heat release rate (kw min m <sup>-2</sup> ) will be minimum for fabric made of
	(A) Wool (B) Cotton / polyester
	(C) Mod acrylic Meta aramid
, , ,	
197.	The steps involved in method study procedure is
	(A) Select – examine – record – develop – install - maintain
	Select – record – examine – develop – install - maintain
	(C) Examine – select – record – develop – install - maintain
٠,,	(D) Record – select – examine – develop – install - maintain
198.	As per SITRA norms, the raw material cost in % is required for 100's combed yarn in
	(B) 58
	(C) 63 (D) 66.5
199.	In a modern mill, the amount of energy consumed by a first passage draw frame for 40 N production is ———————————————————————————————————
*	
	(B) 50 (C) 70 (D) 288
,	(C) 70 (D) 288
200.	As per SITRA norms, in a modern mill, standard load required for lighting systems i per 1000 spindles.
	(A) 10 KW 1 KW
	(C) 5 KW (D) 0.5 KW
•	

## SPACE FOR ROUGH WORK

#### SPACE FOR ROUGH WORK

39 CETET/18 [Turn over